

# **New Construction Logistics**

Presented to: FLSIC

Presented by: Linda Stiles, PEO  
SHIPS-F3

Date: Mar 03

# Table of Contents

## Mission:

*Development, management, execution and evaluation of all aspects of ILS for PEO SHIPS new construction programs*

- Points of Contact
- COSAL Development Process
- SNAP Initialization Process
- SNAP Process to Sailaway and Post Sailaway
- SNAP Process at PSA and Post PSA

# Points of Contact

Linda Stiles

Fleet Support Logistics Director

202-781-2238

stileslk@navsea.navy.mil

LCDR Eduardo Lopez

Fleet Introduction Team Leader

202-781-4871

lopezej@navsea.navy.mil

CDR Tom O'Dowd

Deputy Fleet Support Logistics  
Director

202-781-3480

odowdtb@navsea.navy.mil


Eddie Martin

On-Site Logistics Manager

228-769-4552


martinte@peosnap.navy.mil

# CDMD-OA/SNAP/CDM Database Build



\* For the purpose of this presentation SNAP is synonymous with OPTIMIZED SNAP, OPTIMIZED NTCSS and NTCSS. (RADM, OMMS NG, RSUPPLY)

# COSAL Development



# **OBA Determination Models (Demand Based Sparing)**


- Fleet Logistics Support Improvement Program (FLSIP)
  - Demand Based Models Which Considers Annual Demand and Shipboard Population Only
  - Does Not Consider Cost, Configuration, or Resupply Times
- FLSIP .25 - Parts with 1 Demand In 4 Yrs - Item is Allowed
- FLSIP .10 (MODFLSIP) - Parts with 1 Demand in 10 Yrs - Item is Allowed
- FLSIP .5 Plus - Parts with 1 Demand in 2 Yrs - Item is Allowed
  - Part added back if three CASREP hits on 2 ships in 4 yrs
  - Part added back if eight 3M hits on 2 ships in 2 yrs

**FLSIP .5 PLUS IS CURRENTLY THE ONLY DEMAND BASED SPARING METHOD AUTHORIZED FOR COMPUTATION OF NEW COSALs**

# **OBA Determination Models (Demand Based Sparing)**

- RBS Models determine spares to a required availability target at least cost or spares to a dollar threshold at maximum availability
- AEGIS Optimization Model (AOM)
  - Used on the AEGIS Weapon System
  - Currently being extended across AEGIS platforms
- TIGER/Availability Centered Inventory Model (ACIM)
  - Currently used on ACS and HM&E systems on DDG 51 and some CG 47 Class ships
- All RBS Models take into account:
  - System Configuration
  - Failure Rates/Demand Factors
  - Duty Cycles
  - Item Cost
  - Quantity per end item
  - Requisition response time


# CDMD-OA/SNAP/CDM Database Build




**\* For the purpose of this presentation SNAP is synonymous with OPTIMIZED SNAP, OPTIMIZED NTCSS and NTCSS. (RADM, OMMS NG, RSUPPLY)**




# SNAP Initialization



# Build Process For SPAWARSCEN Norfolk




# CDMD-OA/SNAP/CDM Database Build




\* For the purpose of this presentation SNAP is synonymous with OPTIMIZED SNAP, OPTIMIZED NTCSS and NTCSS. (RADM, OMMS NG, RSUPPLY)


# Update Process To Sailaway



# SNAP Process Post Sailaway




# CDMD-OA/SNAP/CDM Database Build



\* For the purpose of this presentation SNAP is synonymous with OPTIMIZED SNAP, OPTIMIZED NTCSS and NTCSS. (RADM, OMMS NG, RSUPPLY)

# Comparison at End of PSA



BACKUP OF THE  
SHIPBOARD  
SNAP DATABASE

ASI TAPES -  
POST SAILAWAY



PEO SHIPS-F3 SNAP TEAM  
PERFORMS A  
COMPARISON BETWEEN  
THE SHIPBOARD SNAP  
DATABASE AND SUPSHIP /  
SHIPBUILDER DATA

IDENTIFYING 1109 / 1114  
ADDITIONS AND  
SHORTAGE RECORD  
ADDITIONS

# PSA Shipboard Update

